

7/9




FIG. 23A




FIG. 23B

9/89646

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
27 July 2000 (27.07.2000)

PCT

(10) International Publication Number  
**WO 00/43104 A1**

(51) International Patent Classification<sup>7</sup>: B01D 53/34, 49505 (US). BENSON, David, K. [US/US]; 14154 W. 53/92, F01N 3/38 1st Drive, Golden, CO 80401 (US). BURCH, Steven, D. [US/US]; 11 Brigham Circle, Honeoye Falls, NY 14472 (US). HILL, Frederick, B., Jr. [US/US]; 6748 Knollcrest, Rockford, MI 49341 (US). KEYSER, Matthew, A. [US/US]; 2630 S. Miller Dr. #207, Lakewood, CO 80227 (US). MEWS, Lance [US/US]; 4640 6th Street, Caledonia, MI 49316 (US). RIGSBY, Donald, R. [US/US]; 1923 Mulberry Lane, Jenison, MI 49428 (US). TRACY, C., Edwin [US/US]; 19012 W. 60th Drive, Golden, CO 80403 (US).

(21) International Application Number: PCT/US00/01474

(22) International Filing Date: 21 January 2000 (21.01.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: (74) Agent: CARRIER, Robert, J.; Price, Heneveld, Cooper, DeWitt & Linton, 695 Kenmoor, S.E., P.O. Box 2567, Grand Rapids, MI 49501 (US).

60/116.829 22 January 1999 (22.01.1999) US

(71) Applicant (for all designated States except US): BENTELER AUTOMOTIVE CORPORATION [US/US]; Suite 500, 50 Monroe Avenue, N.W., Grand Rapids, MI 49503-2656 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): BIEL, John, P., Jr. [US/US]; 2433 Belknap Avenue, N.E., Grand Rapids, MI

(81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FL, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

*[Continued on next page]*  
**RECEIVED**

DEC 21 2001

**TC 1700**



WO 00/43104 A1

(57) Abstract: A thermally-activated exhaust treatment device, such as a catalytic converter (20), for vehicles includes a core having an inner housing (21) and a catalytic material (27, 27'). A jacket includes an outer housing (22) enclosing the inner housing (21) but characteristically not contacting the inner housing (21). The inner and outer housings (21, 22) includes walls (30, 31) forming a vacuum-drawn sealed insulation cavity (26) around the inner housing (21). A temperature-activated variable insulator device is positioned within the outer housing (22) and includes a hydrogen source (32) and controls for controlling the variable insulator device. A vacuum-maintenance device is incorporated into the insulation cavity (26), and includes a small container, getter material positioned in the container, a porous member allowing gas in the insulation cavity (26) to communicate with the getter material. A multi-layered radiation shield is positioned in the vacuum space and is loosely coupled to the inner housing (21). A vacuum detector includes a visible indicator of the vacuum in the insulation cavity (26).